

WatchGuard® XTM 3 Series

WITH A NEXT-GENERATION XTM 3 SERIES SECURITY SOLUTION, YOUR NETWORK IS:

SECURE

- Application-layer content inspection recognizes and blocks threats that stateful packet firewalls cannot detect.
- Wide-ranging proxy protection provides robust security on HTTP, HTTPS, FTP, SMTP, POP3, DNS, TCP/UDP.
- A suite of security subscriptions boosts protection in critical attack areas for complete threat management.
- Optional Application Control keeps unproductive, inappropriate, and dangerous apps off-limits.

FAST and EFFICIENT

- Up to 1.4 Gbps firewall throughput and up to 240 Mbps VPN throughput keep data moving.
- Up to seven 1GgE ports support high-speed LAN backbone infrastructures and gigabit WAN connections.
- Interactive, real-time monitoring and reporting – at no additional charge – give an unprecedented view into network security activity so you can take immediate preventive or corrective actions.
- Includes the “Pro” version of the Fireware® XTM operating system for advanced networking features, including VLAN support, multi-WAN load balancing, and dynamic routing.
- Intuitive management console centrally manages all security functions.
- Role-based access control (RBAC) allows lead administrators to create custom roles for granular control.
- Drag-and-drop Branch Office VPN setup – three clicks and your remote office is connected.

FLEXIBLE

- WAN and VPN failover provide redundancy for increased reliability.
- Multiple VPN choices (SSL and IPSec) for flexibility in remote access, including support for Apple iOS devices such as the iPhone, iPad, and iPod touch.
- To maximize port utilization, any of the ports can be configured as Trusted, External, or DMZ.
- Choose the form factor that suits your needs – XTM 330 is rack mount, XTM 33/33-W is tabletop.

WIRED OR WIRELESS – YOUR CHOICE

- The XTM 33-W wireless model includes optional dual-band 802.11n technology for much more responsive wireless network connections and expanded range. Allows users to access 2.4 GHz or less crowded 5 GHz band.
- Multiple security zones give administrators precise control over Internet access privileges for different user groups.
- Wireless guest services segment the Internet for customers/guests.

PREPARED FOR TOMORROW’S CHALLENGES

- Multi-layered, interlocking security protects the network while throughput remains high. No need to compromise protection for strong performance or vice versa.
- Advanced networking features ensure reliability and the flexibility to meet changing business requirements.
- Secure remote connectivity keeps the mobile workforce online and productive.
- Monitoring and reporting tools, included at no extra cost, support industry and regulatory compliance, with drill-down functions that make it easy to pinpoint specific activities.



XTM 3 SERIES	XTM 33	XTM 33-W	XTM 330
THROUGHPUT & CONNECTIONS			
Firewall throughput*	850 Mbps	850 Mbps	1.4 Gbps
VPN throughput*	100 Mbps	100 Mbps	240 Mbps
AV throughput*	175 Mbps	175 Mbps	340 Mbps
IPS throughput*	238 Mbps	238 Mbps	480 Mbps
UTM throughput*	100 Mbps	100 Mbps	190 Mbps
Interfaces 10/100/1000	5 copper	5 copper	7 copper
I/O interfaces	1 Serial 1 USB	1 Serial 1 USB	1 Serial 2 USB
Nodes supported (LAN IPs)	Unrestricted	Unrestricted	Unrestricted
Concurrent connections (bi-directional)	40,000	40,000	40,000
New connections per second	3,800	3,800	5,500
VLANs bridging, tagging, routed mode	75	75	75
Authenticated users limit	500	500	500
WSM licenses (incl)	4	4	4
Wireless available	–	802.11a/b/g/n	–
VPN TUNNELS			
Branch Office VPN	50	50	50
Mobile VPN IPsec (incl/max)	5/55	5/55	5/55
Mobile VPN SSL	55	55	55
SECURITY FEATURES			
Firewall	Stateful packet inspection, deep packet inspection, proxy firewall		
Application proxies	HTTP, HTTPS, SMTP, FTP, DNS, TCP, POP3		
Threat protection	Blocks spyware, DoS attacks, fragmented packets, malformed packets, blended threats, and more		
VoIP	H.323, SIP, call setup and session security		
Security subscriptions	Application Control, Intrusion Prevention, Gateway AV, Reputation Enabled Defense, WebBlocker, spamBlocker		
VPN & AUTHENTICATION			
Encryption	DES, 3DES, AES 128-, 192-, 256-bit		
IPSec	SHA-1, MD5, IKE pre-shared key, 3rd party cert		
VPN failover	Yes		
SSL	Thin client, Web exchange		
PPTP	Server and Passthrough		
Single sign-on	Transparent Active Directory Authentication		
XAUTH	RADIUS, LDAP, Secure LDAP, Windows Active Directory		
Other user authentication	VASCO, RSA SecurID, web-based, local, Microsoft Terminal Services and Citrix		
MANAGEMENT			
Management platform	WatchGuard System Manager (WSM) v11 or higher		
Alarms and notifications	SNMP v2/v3, Email, Management System Alert		
Server support	Logging, Reporting, Quarantine, WebBlocker, Management		
Web UI	Supports Windows, Mac, Linux OS		
Command line interface	Includes direct connect and scripting		
STANDARD NETWORKING			
QoS	8 priority queues, DiffServ, modified strict queuing		
IP address assignment	Static, DHCP (server, client, relay), PPPoE, DynDNS		
CERTIFICATIONS			
Security	ICSA Firewall, ICSA VPN, EAL4+ Review Pending: FIPS 140-2		
Safety	NRTL/C, CB		
Network	IPv6 Ready Gold (routing)		
Control of hazardous substances	WEEE, RoHS, REACH		

*Throughput rates will vary based on environment and configuration. Contact your WatchGuard reseller or call WatchGuard directly (1.800.734.9905) for help determining the right model for your network.



POWERED BY FIREWARE XTM PRO

XTM 3 Series appliances ship with the Pro version of the Fireware XTM operating system. Advanced networking features[†] include:

NETWORKING FEATURES	FIREWARE XTM PRO
Routing	Static / Dynamic (BGP4, OSPF, RIP v1/v2) / Policy-based
High Availability [†]	Active/passive, active/active with load balancing
NAT	Static, dynamic, 1:1, IPsec traversal
Other Features	High Availability, [†] Port Independence, WAN failover, Multi-WAN load balancing, Transparent/drop-in mode

[†]High Availability is not currently available on 33-W. Server load balancing is not available on 3 Series appliances.

DIMENSIONS AND POWER

PRODUCT DIMENSIONS

33 Wired	6.1" x 7.5" x 1.25" (15.5 x 19.0 x 3.2 cm)
33 Wireless (antennae up)	7.75" x 10.75" x 5" (19.7 x 27.3 x 12.7 cm)
330	11.25" x 17" x 1.75" (28.6 x 43.2 x 4.5 cm)

SHIPPING DIMENSIONS

33 Wired or Wireless	10.75" x 13.25" x 3.4" (27.3 x 33.7 x 8.6 cm)
330	18" x 21" x 5.25" (45.7 x 53.3 x 13.3 cm)

SHIPPING WEIGHT

33 Wired / Wireless	3.2 lbs (1.45 Kg) / 3.6 lbs (1.6 Kg)
330	16.1 lbs (7.3 Kg)

POWER CONSUMPTION

33 Wired	U.S. 23.33 Watts (80 BTU/hr)
33 Wireless	U.S. 24.0 Watts (82 BTU/hr)
330	U.S. 50 Watts (171 BTU/hr)

AC POWER

100-240 VAC Autosensing

RACK MOUNTABLE

1U rack mount kit included with XTM 330 only
--

Environment

OPERATING	STORAGE
TEMPERATURE	
33 Wired or Wireless	32° F to 104° F 0° C to 40° C
330	32° F to 104° F 0° C to 40° C

RELATIVE HUMIDITY

10% to 85% non-condensing	10% to 95% non-condensing
---------------------------	---------------------------

ALTITUDE

33 Wired or Wireless	0 to 9,843 ft @ 95° F (3,000 m @ 35° C)
330	0 to 9,843 ft at 95° F (3,000 m at 35° C)

MTBF

33 Wired or Wireless	129,955 hours @ 104° F (40° C)
330	51,644 hours @ 77° F (25° C)

EXPERT GUIDANCE AND SUPPORT

A subscription to LiveSecurity® Service is included with every XTM 3 appliance for hardware warranty, technical support, and software updates. Renewable in multi-year subscriptions.

BUY THE BUNDLE AND GET THE WORKS!

Get everything you need for complete threat management at a great price with the Security Bundle. Includes XTM 3 Series appliance and subscriptions to Application Control, Gateway AV, spamBlocker, WebBlocker, Intrusion Prevention Service, Reputation Enabled Defense, and LiveSecurity.** A great deal when you buy together and save!

**XTM 33/33-W Bundle includes standard LiveSecurity with 12/5 tech support. XTM 330 Bundle includes LiveSecurity Plus with 24/7 tech support.